

Please click here for the full version of this document – redistribution is subject to ASCE license or copyright. <http://www.ascelibrary.org/>

EFFECTS OF RECLAIMED ASPHALT SHINGLES ON ENGINEERING PROPERTIES OF SOILS

Fred Hooper¹, Member, Geo-Institute, and
W. Allen Marr², P.E., Fellow, Geo-Institute

ABSTRACT: Over 7.3-million tons of waste asphalt roofing shingles are generated each year in the US, and beneficial uses are needed to avoid costly disposal in landfills. Construction firms and state DOTs have investigated blending ground shingles with soils for use in pavement structures. These studies indicated that the addition of shingles had beneficial effects on some soils, however only qualitative observations were made. The objective of this study was to obtain some baseline quantitative data on the physical and mechanical effects that shingles have on soils. We added shingles to a crushed stone gravel, a silty sand, clean sand, and a clay. This work showed that for weak materials like clays, 25.4 mm (1-inch) minus shingles can potentially improve their strength. For inherently strong granular materials like gravels and sands, shingles can potentially diminish their strength from initially high values. However, the results indicate that these materials mixed with shingles can still provide adequate subgrade support for pavements and light structures.

¹Project Manager, GeoTesting Express, Inc., 1145 Massachusetts Avenue, Boxborough, MA 01719, fhooper@geotesting.com

²Chief Engineer, GeoTesting Express, Inc., 1145 Massachusetts Avenue, Boxborough, MA 01719, wam@geotesting.com