

**ROCK CHAIN OF CUSTODY & TEST REQUEST**

| CLIENT            |         |
|-------------------|---------|
| Company:          |         |
| Address:          |         |
| City, State, Zip: |         |
| Contact:          | E-mail: |
| Phone:            | Fax:    |

| PROJECT           |                   |
|-------------------|-------------------|
| Project Name:     |                   |
| Address:          | Client Project #: |
| City, State, Zip: |                   |
| On-site Contact:  | E-mail:           |
| Phone:            | Fax:              |

GeoTesting Express, Inc.  
1145 Massachusetts Avenue  
Boxborough, MA 01719  
800 434 1062 Toll Free  
978 635 0266 Fax

2662 Holcomb Bridge Road, Suite 310  
Alpharetta, GA 30022  
770 645 6575 Tel  
770 645 6570 Fax

[www.geotesting.com](http://www.geotesting.com)

| INVOICE (complete if different from client) |         |
|---|---------|
| Company:                                    |         |
| Address:                                    |         |
| City, State, Zip:                           |         |
| Contact:                                    | E-mail: |
| Phone:                                      | Fax:    |

| GENERAL           |   |
|-------------------|---|
| Purchase Order #: | GTX Sales Order #:  |
| Shipped By:       | Date Shipped:   |
| Mode of Shipment: | Requested Turnaround:   |
| Send Results To:  | <input type="checkbox"/> CLIENT OFFICE <input type="checkbox"/> PROJECT OFFICE  |
| Send Results Via: | <input type="checkbox"/> E-MAIL <input type="checkbox"/> FAX <input type="checkbox"/> VERBAL <input type="checkbox"/> HARD COPY |

| ROCK      |   | Cerchar Abrasivity | Direct Shear (ASTM D 5607)<br>*specify conditions below | Direct Tensile Strength (ASTM D 2936) | Elastic Moduli in Triaxial Compression (ASTM D 7012 Method B/D 5407)<br>specify conditions below | Elastic Moduli in Uniaxial Compression (ASTM D 7012 Method D/ D3148) | Freeze-Thaw Durability (ASTM D 5312) | Wet-Dry Durability (ASTM D 5313) | Air Permeability (ASTM D 4525) | Petrographic Analysis (ISRM) | Point Load Index (ASTM D 5731) | Punch Penetration | Pulse Velocities and Ultrasonic Constants (ASTM D 2845) | Slake Durability (ASTM D 4644) | Splitting (Brazilian) Tensile Strength (ASTM D 3967) | Total Hardness (Schmidt Hammer and Taber Abrasion) | Triaxial Compression (ASTM D 7012 Method A/D 2664)<br>specify conditions below | Unconfined Compression (ASTM D 7012 Method C/D 2938) | Other: _____ | Other: _____ |
|-----------|---|--------------------|---|---------------------------------------|--|--|--------------------------------------|----------------------------------|--------------------------------|------------------------------|--------------------------------|-------------------|---|--------------------------------|--|--|--|--|--------------|--------------|
| Sample ID | *please include core run # and depth if known |                    |   |                                       |  |  |                                      |                                  |                                |                              |                                |                   |   |                                |  |  |  |  |              |              |
| 1         |   |                    |   |                                       |  |  |                                      |                                  |                                |                              |                                |                   |   |                                |  |  |  |  |              |              |
| 2         |   |                    |   |                                       |  |  |                                      |                                  |                                |                              |                                |                   |   |                                |  |  |  |  |              |              |
| 3         |   |                    |   |                                       |  |  |                                      |                                  |                                |                              |                                |                   |   |                                |  |  |  |  |              |              |
| 4         |   |                    |   |                                       |  |  |                                      |                                  |                                |                              |                                |                   |   |                                |  |  |  |  |              |              |
| 5         |   |                    |   |                                       |  |  |                                      |                                  |                                |                              |                                |                   |   |                                |  |  |  |  |              |              |
| 6         |   |                    |   |                                       |  |  |                                      |                                  |                                |                              |                                |                   |   |                                |  |  |  |  |              |              |

\*Specify Test Conditions (Test Normal Loads, Test Confining Stresses, etc.):

|                                  |                   |             |
|----------------------------------|-------------------|-------------|
| AUTHORIZE BY SIGNING AND DATING: |                   |             |
| SIGNATURE: _____                 | PRINT NAME: _____ | DATE: _____ |

|                  |       |              |       |
|------------------|-------|--------------|-------|
| Relinquished By: | DATE: | Received By: | DATE: |
|                  | TIME: |              | TIME: |
| Relinquished By: | DATE: | Received By: | DATE: |
|                  | TIME: |              | TIME: |