EROSION TESTS ON SAMPLES FROM THE NEW ORLEANS LEVEES

J.-L. Briaud¹, H.-C. Chen², A.V. Govindasamy³, R. Storesund⁴

¹Professor and Holder of the Buchanan Chair, Zachry Department of Civil Engineering, Texas A&M University, College Station, Texas 77843-3136, USA (<u>briaud@tamu.edu</u>) ²Professor, Zachry Department of Civil Engineering, Texas A&M University, College Station, Texas 77843-3136, USA

³PhD Candidate, Zachry Department of Civil Engineering, Texas A&M University, College Station, Texas 77843-3136, USA

⁴PhD Candidate, Department of Civil and Environmental Engineering, Davis Hall, University of California, Berkeley, California.

ABSTRACT

Twenty three samples were retrieved from eleven locations at the top of the levees around New Orleans. Thirteen were samples from Shelby tubes while ten were bag samples. These samples were tested in the EFA ort Erosion Function Apparatus. The results of such an erosion test is an erosion function which links the erosion rate in mm/hr to the water velocity in m/s. The results obtained show a large variation of erosion resistance among the soils tested and point to the need to evaluate the remaining levees. New ideas for such an evaluation and for improving the redundancy of such long linear systems are presented.

Please click here for the full version of this document - redistribution is subject to ASCE license or copyright. http://www.ascelibrary.org

1