

## FLOWTRAC II

The FlowTrac II is an intelligent flow pump that regulates pressure and volume in a test cell automatically. It incorporates a high speed, precision micro-stepper motor and can maintain a desired pressure within 0.35 kPa (0.05 psi) while monitoring volume change within 0.001 cc (0.00003 fl/oz). FlowTrac II units are used to provide cell pressure and back pressure in triaxial testing, back pressure for constant rate of strain consolidation testing, and cell pressure, inflow pressure, and outflow pressure for permeability testing.

Technical Specifications		
<b>VOLUME CAPACITY</b>		
250 cc (8.5 fl oz) or 750 cc (25.4 fl oz)		
<b>PRESSURE CAPACITY</b>		
200 psi (1400 kPa) or 500 psi (3500 kPa)		
<b>FLOW RATE</b>		
Min Speed	0.0003 cc/min	0.00001 fl oz/min
Max Speed	1054 cc/min	36 fl oz/min
<b>MOTOR</b>		
Micro-stepper system with built-in controls		
<b>POWER</b>		
110/220 V, 50/60 Hz, 1 phase		
<b>DIMENSIONS</b>		
203 x 406 x 470 mm (8 x 16 x 18.5 in)		
<b>WEIGHT</b>		
14 kg (30 lbs)		
<b>INCLUDED</b>		
<ul style="list-style-type: none"> <li>• GeoNet-U USB 2.0 network adapter and cable to link to PC/laptop</li> <li>• Associated module to automatically run and report tests</li> </ul>		
<b>WARRANTY</b>		
12 month warranty; extended warranties available		
<b>TESTING CAPABILITIES</b>		
<ul style="list-style-type: none"> <li>• Semi-Automated Permeability</li> </ul> <p>Addition of LoadTrac II or III:</p> <ul style="list-style-type: none"> <li>• Triaxial (UU, CU, CD) and Stress Path</li> <li>• Fully Automated Permeability</li> <li>• Constant Rate Consolidation</li> <li>• Cyclic Triaxial (with Electromechanical Actuator)</li> </ul>		



FlowTrac II System